

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

**Motor type:** 7CV3314C **SIMOTICS SD - 315L - IM B3 - 6 p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

**Electrical data**

**Safe Area**

U	$\Delta/Y$	f	P	P	I	n	M	M	$\eta^{3)}$			$\cos\phi^{3)}$			$I_A/I_N$	$M_A/M_N$	$M_K/M_N$	IE-CL
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4				

**Motordaten / Motor Data**

415	$\Delta$	50	110.00	-/-	188.00	991	108.0	1060.0	95.6	95.7	95.5	0.85	0.81	0.72	7.5	3.0	3.2	IE3
-----	----------	----	--------	-----	--------	-----	-------	--------	------	------	------	------	------	------	-----	-----	-----	-----

IM B3 / IM 1001	FS 315L	1020 kg	SF:1	IS 12615 / IEC 60034-1	-
-----------------	---------	---------	------	------------------------	---

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 12 s | 20 s

**Mechanical data**

Sound pressure level 50Hz   60Hz	75 dB(A)   78 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia   Rotor GD <sup>2</sup>	4.1938 kg m <sup>2</sup>   16.7752 kgf.m <sup>2</sup>	Vibration severity grade	A (Standard)
Bearing DE   NDE	6319 C3   6319 C3	Insulation	155(F) utilized to 130(B)
<b>bearing lifetime</b>		Duty type	S1
L <sub>10mh</sub> F <sub>Rad max</sub> according catalogue 50 60Hz <sup>1)</sup>	20.000 h   16.000 h	Direction of rotation	Bidirectional
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup>	50.000 h   40.000 h	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE	Forced ventilation motor details	- / -
Relubrication interval/quantity DE   NDE	40 g   40 g 6.000 h	Net weight of the motor (IM B3)	1020 kg
Type of construction	IM B3 / IM 1001	Rotor weight	326 kg
Degree of protection	IP55	Data of anti condensation heating	-/ V, -/ W
Lubricants	Esso Unirex N3	Coating (paint finish)	Standard paint finish
Regreasing device	Yes (standard)	Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A	Motor protection	(A) without
Condensate drainage holes	Yes	Method of cooling	IC411 - Self ventilated, surface cooled

**Terminal box**

Terminal box position	Top	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Material of terminal box	Cast iron	Cable entry	2xM63x1.5
Type of terminal box	TB1 Q01	Cable gland	2 Plugs
Contact screw thread	M12		
Max. cross-sectional area	185 mm <sup>2</sup>		

**Notes:**

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_K/M_N$  = break down torque / nominal torque

3) Value is valid only for DOL operation with motor design IC411

1) L10mh according to DIN ISO 281 10/2010

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>	
	document type datasheet			document status released		
	MLFB and Order Code 1LE7503-3AC43-5AA4			document number		
© Siemens AG 2022		rev. 01	creation date 2022-09-30	language en		Page 1/1