

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type: **7CV3094B** SIMOTICS SD - 90L - IM B3 - 4 p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ/Y	f	P	P	I	n	M	M	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4				
Motordaten / Motor Data																		
415	Y	50	1.50	-/-	3.10	1444	1.0	9.9	85.6	85.8	84.0	0.78	0.71	0.58	6.5	3.0	3.1	IE3
IM B3 / IM 1001			FS 90L		29 kg		SF:1		IS 12615 / IEC 60034-1									
Environmental conditions : -20 °C - +50 °C / 1,000 m										Locked rotor time (hot / cold) : 12 s 18 s								



Mechanical data

Sound pressure level 50Hz 60Hz	62 dB(A)	65 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia Rotor GD ²	0.0044 kg m ² 0.0175 kgf.m ²		Vibration severity grade	A (Standard)
Bearing DE NDE	6205 2ZC3	6204 2ZC3	Insulation	155(F) utilized to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad max} according catalogue 50 60Hz ¹⁾	20.000 h	16.000 h	Direction of rotation	Bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	50.000 h	40.000 h	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE		Forced ventilation motor details	- / -
Relubrication interval/quantity DE NDE	- / g - / g - / h		Net weight of the motor (IM B3)	29 kg
Type of construction	IM B3 / IM 1001		Rotor weight	5 kg
Degree of protection	IP55		Data of anti condensation heating	- / V, - / W
Lubricants	Esso Unirex N3		Coating (paint finish)	Standard paint finish
Regreasing device	- / -		Color, paint shade	RAL7030
Grease nipple	- / -		Motor protection	(A) without
Condensate drainage holes	No		Method of cooling	IC411 - Self ventilated, surface cooled

Terminal box

Terminal box position	Top	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Material of terminal box	Aluminium	Cable entry	1xM16x1.5+1xM25x1.5
Type of terminal box	TB7 D04	Cable gland	2 Plugs
Contact screw thread	M4		
Max. cross-sectional area	6 mm ²		

Notes:
 I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 3) Value is valid only for DOL operation with motor design IC411
 1) L10mh according to DIN ISO 281 10/2010

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
SIEMENS	document type datasheet			document status released	
	MLFB and Order Code 1LE7503-0EB42-3AA4			document number	
© Siemens AG 2022		rev. 01	creation date 2022-09-30	language en	