

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type: **7CV3104C** SIMOTICS SD - 100L - IM B3 - 6 p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

## Electrical data

## Safe Area

U	$\Delta/Y$	f	P	P	I	n	M	M	$\eta^{3)}$			$\cos\phi^{3)}$			$I_A/I_N$	$M_A/M_N$	$M_k/M_N$	IE-CL
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4				
<b>Motordaten / Motor Data</b>																		
415	Y	50	1.50	-/-	3.40	953	1.5	15.0	83.6	84.4	82.8	0.73	0.65	0.52	5.0	2.8	3.1	IE3
IM B3 / IM 1001			FS 100L		33 kg		SF:1		IS 12615 / IEC 60034-1									
Environmental conditions : -20 °C - +50 °C / 1,000 m										Locked rotor time (hot / cold) : 18 s   26 s								



## Mechanical data

Sound pressure level 50Hz   60Hz	61 dB(A)   64 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia   Rotor GD <sup>2</sup>	0.0084 kg m <sup>2</sup>   0.0335 kgf.m <sup>2</sup>	Vibration severity grade	A (Standard)
Bearing DE   NDE	6206 2ZC3   6206 2ZC3	Insulation	155(F) utilized to 130(B)
<b>bearing lifetime</b>		Duty type	S1
L <sub>10mh</sub> F <sub>Rad max</sub> according catalogue 50 60Hz <sup>1)</sup>	20.000 h   16.000 h	Direction of rotation	Bidirectional
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup>	50.000 h   40.000 h	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE	Forced ventilation motor details	- / -
Relubrication interval/quantity DE   NDE	- / - g   - / - g - / - h	Net weight of the motor (IM B3)	33 kg
Type of construction	IM B3 / IM 1001	Rotor weight	8 kg
Degree of protection	IP55	Data of anti condensation heating	- / V, - / W
Lubricants	Esso Unirex N3	Coating (paint finish)	Standard paint finish
Regreasing device	- / -	Color, paint shade	RAL7030
Grease nipple	- / -	Motor protection	(A) without
Condensate drainage holes	Yes	Method of cooling	IC411 - Self ventilated, surface cooled

## Terminal box

Terminal box position	Top	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Material of terminal box	Aluminium	Cable entry	2xM32x1.5
Type of terminal box	TB7 F04	Cable gland	2 Plugs
Contact screw thread	M5		
Max. cross-sectional area	16 mm <sup>2</sup>		

**Notes:**  
 $I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_k/M_N$  = break down torque / nominal torque  
 3) Value is valid only for DOL operation with motor design IC411  
 1) L10mh according to DIN ISO 281 10/2010

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	<a href="#">Link documents</a>
<b>SIEMENS</b>	document type datasheet			document status released	
	MLFB and Order Code 1LE7503-1AC42-3AA4			document number	
© Siemens AG 2022		rev. 01	creation date 2022-09-30	language en	