

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type: **7CV3112D** SIMOTICS SD - 112M - IM B3 - 8 p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ/Y	f	P	P	I	n	M	M	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4				

Motordaten / Motor Data

415	Y	50	1.50	-/-	4.10	704	2.1	20.4	79.7	79.7	75.7	0.64	0.56	0.43	4.0	1.7	2.3	IE3
-----	---	----	------	-----	------	-----	-----	------	------	------	------	------	------	------	-----	-----	-----	-----

IM B3 / IM 1001	FS 112M	50 kg	SF:1	IS 12615 / IEC 60034-1	-
-----------------	---------	-------	------	------------------------	---

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 12 s | 25 s

Mechanical data

Sound pressure level 50Hz 60Hz	79 dB(A)	82 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia Rotor GD ²	0.0136 kg m ² 0.0543 kgf.m ²		Vibration severity grade	A (Standard)
Bearing DE NDE	6206 2ZC3	6206 2ZC3	Insulation	155(F) utilized to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad max} according catalogue 50 60Hz ¹⁾	20.000 h	16.000 h	Direction of rotation	Bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	50.000 h	40.000 h	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE		Forced ventilation motor details	- / -
Relubrication interval/quantity DE NDE	- / - g - / - g - / - h		Net weight of the motor (IM B3)	50 kg
Type of construction	IM B3 / IM 1001		Rotor weight	11 kg
Degree of protection	IP55		Data of anti condensation heating	- / V, - / W
Lubricants	Esso Unirex N3		Coating (paint finish)	Standard paint finish
Regreasing device	- / -		Color, paint shade	RAL7030
Grease nipple	- / -		Motor protection	(A) without
Condensate drainage holes	Yes		Method of cooling	IC411 - Self ventilated, surface cooled

Terminal box

Terminal box position	Top	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Material of terminal box	Aluminium	Cable entry	2xM32x1.5
Type of terminal box	TB7 F04	Cable gland	2 Plugs
Contact screw thread	M5		
Max. cross-sectional area	16 mm ²		

Notes:



I_A/I_N = locked rotor current / current nominal

M_A/M_N = locked rotor torque / torque nominal

M_K/M_N = break down torque / nominal torque

3) Value is valid only for DOL operation with motor design IC411

1) L10mh according to DIN ISO 281 10/2010

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet	document status released			
	MLFB and Order Code 1LE7503-1BD22-3AA4	document number			
© Siemens AG 2022	rev. 01	creation date 2022-09-30	language en		Page 1/1